

BIX[®] STAIN PUTTY[™]

MATERIAL SAFETY DATA SHEET

COMPANY NAME AND ADDRESS: NFPA Rating: H=0, F=0, R=0

Office:	Plant:	(24 HOUR) EMERGENCY PHONE:
BIX MFG. CO.	BIX MFG. CO.	INFOTRAC: (800) 535-5053
P.O. Box	2011 Ashland City Hwy.	<i>Effective:</i> October 23, 2000
Ashland City, TN 37015	Ashland City, TN 37015	<i>Supersedes:</i> April 1, 1997
PHONE: (615) 792-3260 / (800) 251-1098		
Internet: www.bixmfg.com		

HAZARDOUS INGREDIENTS:

N/A

PHYSICAL DATA:

Boiling Point	N/A	Hardening Time	27-37 minutes
Vapor Pressure Formulation	Not determined		
Vapor Density (Calculated)	Not determined	Appearance	Light brown odorless powder
Solubility in Water	0.2%	Specific Gravity	2.7

FIRE AND EXPLOSION HAZARD DATA:

Flash Point: (Pensky-Martens CC)	N/A	Flammable Limits in Air	Not determined
Extinguisher Media	Water spray, dry chemical, carbon dioxide, and/or foam.		
Special Fire Fighting Procedures	N/A		
Unusual Fire and Explosion Hazards	None		

PHYSICAL HAZARDS / REACTIVITY DATA:

Stability	Stable	Conditions to Avoid	High temperatures
-----------	--------	---------------------	-------------------

SPECIAL PRECAUTIONS FOR SAFE HANDLING AND USE:

Handling and Storage	Dew point conditions, or other conditions causing presence of liquid, will harden putty during storage.
Material Release or Spill	Avoid creating excessive dust. Slurry may plug drains.
Waste Disposal	Normal disposal as for any dry inert powder.

HEALTH HAZARD DATA:

Route of Entry: Inhalation: Yes Skin: Yes Ingestion: Yes

Chemical ingredients listed as a carcinogen or potential carcinogen:

National Toxicology Program: None IARC Monographs: None OSHA Regulated: None

Signs and Symptoms of Exposure:

Skin Contact may develop sufficient heat to cause burns if a large mass, such as a cast of a hand or arm, is kept in contact with skin while hardening. May dry skin.

Eyes Contact causes irritation. Symptoms are tearing, redness and discomfort.

Inhalation: Vapors unlikely due to physical properties.

Ingestion: Powder hardens when wet and if ingested may result in an obstruction.

Medical Conditions That May Be Aggravated by Exposure to This Product:

Preexisting eye and skin disorders.

Emergency and First Aid Procedures for Overexposure:

Inhalation: If affected, move to fresh air.

Eyes Immediately flush with water for 15 minutes while lifting eyelids and rolling eyes. Get medical attention if irritation persists.

Skin Remove contaminated clothing and shoes. Wash exposed areas thoroughly with water. Launder contaminated clothing before reuse. Get prompt medical attention.

Ingestion Plaster hardens when wet and if ingested may result in an obstruction. Hardening time is approximately 27 - 37 minutes. See physician.

SPECIAL PROTECTION AND CONTROL MEASURES:

Respiratory Protection Wear an OSHA approved respirator when nuisance dust is excessive.

Ventilation: General ventilation.

Eye Protection: Dust goggles or safety glasses.

Other Protective Equipment: None required

Work Hygiene Practices: Do not swallow. Avoid contact with skin and eyes. Have water available for rinsing if contact should occur.

Note: Personal protection information given is based upon the general information as to normal uses and conditions. Where special or unusual uses or conditions exist, it is suggested that the expert assistance of an industrial hygienist or other qualified professional be sought.

The data contained herein is based on information currently available to BIX Mfg. Co., Incorporated and is believed to be factual. As a formulator, blender, and compounder, BIX Mfg. Co., Incorporated does not manufacture the raw materials used in this product and correspondingly relies on information provided to BIX Mfg. Co., Incorporated from material safety data sheets on the specific raw materials in the construction of this material safety data sheet. Such information is to the best of BIX Mfg. Co., Incorporated's knowledge and belief to be accurate and reliable as of the date of this MSDS. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE AS TO THE ACCURACY, RELIABILITY, OR COMPLETENESS. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular application. This information is not intended to be all-inclusive as to the manner and conditions of use, handling and storage. Other factors may involve other or additional safety or performance considerations. This data is not to be taken as a warranty or representation of which BIX Mfg. Co., Incorporated assumes legal responsibility.