

Material Safety Data Sheet

Revision Date 29-Sep-2010

1. CHEMICAL PRODUCT AND COMPANY INFORMATION

Product code 19911
Product name White Lube
Recommended Use Lubricant

Supplier Lawson Products, Inc.
1666 East Touhy Avenue
Des Plaines, IL 60018
(847)-827-9666

Emergency telephone number (888) 426-4851

2. HAZARDS IDENTIFICATION

Emergency Overview
Flammable. Irritant.

Aggravated Medical Conditions

None Known

Principal Routes of Exposure

Eyes. Skin contact. Inhalation. Ingestion. Skin absorption.

Potential health effects

Eyes Contact with eyes may cause irritation.

Skin May cause the following effects: . Skin Irritation. Dermatitis. Repeated or prolonged exposure may cause: . Redness. Frostbite. Possible burns to tissue. May be absorbed through the skin in harmful amounts.

Inhalation May cause the following effects. Shortness of breath. Dizziness. Light headedness. Extreme overexposure may cause. Liver damage. Kidney damage. Possible asphyxiation. Misuse by deliberately concentrating vapors and inhaling contents can be harmful or fatal.

Ingestion May be harmful if swallowed. Gastrointestinal irritation. Aspiration hazard. May cause severe lung damage if aspirated into the lungs from ingestion or vomiting.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Hexane	110-54-3	34-39
Stoddard solvent	8052-41-3	25-30
Zinc oxide	1314-13-2	1-6
Butane	106-97-8	6-11
Propane	74-98-6	8-13

Petroleum distillates, hydrotreated heavy naphthenic	64742-52-5	24-29
--	------------	-------

4. FIRST AID MEASURES

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 20 minutes. Seek medical attention.

Skin contact Wash area thoroughly with soap and water.

Ingestion If a large quantity of liquid is swallowed, do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person. Seek medical attention.

Inhalation Remove to fresh air. Provide oxygen if breathing is difficult. If not breathing, give artificial respiration. Keep warm and quiet. Seek medical attention.

5. FIRE FIGHTING MEASURES

Flash point °C No data available
Flash point °F No data available
Method No information available

Autoignition temperature °C No data available
Autoignition temperature °F No data available

Flammability Limits (% in Air)
Upper 9.5%
Lower 1.2%

Suitable extinguishing media

Water fog. Carbon dioxide (CO₂). Dry chemical. Foam. Alcohol foam.

Special protective equipment for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Fire and Explosion Hazards

Flammable . Evacuate area of unprotected and unnecessary personnel. Material is highly volatile and readily gives off vapors. Vapors are heavier than air and may travel along the ground to an ignition source distant from material handling area. Possible ignition sources include pilot lights, flames, lighted cigarettes, heating elements, electric motors, sparks from electrical switches. Water should be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat .

Sensitivity to shock

No information available.

Sensitivity to static discharge

No information available.

6. ACCIDENTAL RELEASE MEASURES

6. ACCIDENTAL RELEASE MEASURES

Methods for cleaning up

Shut off source of leak if safe to do so. Evacuate area of unprotected and unnecessary personnel. Ventilate area to maintain exposure below permissible exposure limits. Dike or dam large spills. Soak up excess with absorbent material. Dispose of absorbent in accordance with local, state and federal regulations. Do not allow product to reach sewage system, soil, surface or ground water, or any water course. Notify proper authorities if entry occurs.

7. HANDLING AND STORAGE

Handling

Keep container closed when not in use.

Storage

Keep container tightly closed. Keep away from direct sunlight. Keep away from open flames, hot surfaces and sources of ignition. Store in temperatures below 120 degrees F. Containers exposed to extreme heat may burst.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Chemical Name	OSHA PEL (TWA)	OSHA PEL (Ceiling)	ACGIH OEL (TWA)	ACGIH OEL (STEL)
Hexane	1800 mg/m ³ 500 ppm	-	50 ppm	N/D
Stoddard solvent	2900 mg/m ³ 500 ppm	-	100 ppm	-
Petroleum distillates, hydrotreated heavy naphthenic	-	-	-	-
Propane	1000 ppm 1800 mg/m ³	-	1000 ppm	-
Butane	800 ppm	-	1000 ppm	-
Zinc oxide	15 mg/m ³ total 5 mg/m ³	-	2 mg/m ³	10 mg/m ³

Ventilation and Environmental Controls

Use enough ventilation, local exhaust at the work area, general, or both, to keep below the TLV's in the worker's breathing zone and the general area. If current ventilation practices are not adequate in maintaining airborne concentrations below the established exposure limits, additional ventilation or exhaust systems may be required. Use with adequate explosion-proof ventilation to meet the limits in Section 8.

Hygiene measures

Remove and wash contaminated clothing before re-use.

Other precautions

Use personal protective equipment.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand Protection

Gloves are recommended to prevent prolonged or repeated contact. Protective gloves.

Eye protection

Safety glasses with side-shields.

Skin and body protection

None necessary under normal conditions

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	Aerosol
Color	Clear
Odor	Solvent
Odor Threshold	No information available
pH	Not Applicable
Specific Gravity	No data available
Vapor pressure	No data available
Vapor density	No data available
Evaporation Rate	<1 (ether = 1)
Water solubility	No data available
VOC Content	74.38%
Partition Coefficient (n-octanol/water)	No data available
Boiling point/range °C	No data available
Boiling point/range °F	No data available
Melting point/range °C	No data available
Melting point/range °F	No data available
Flash point °F	No data available

10. STABILITY AND REACTIVITY

Stability

Stable under normal conditions.

Conditions to avoid

Heat, flames and sparks.

Incompatibility

Strong oxidizing agents.

Hazardous Decomposition Products

Carbon dioxide. Carbon monoxide.

Polymerization

Will not occur.

11. TOXICOLOGICAL INFORMATION**Component Information**

Chemical Name	LD50 (oral, rat)	LD50 (dermal, rat/rabbit)	LC50 (inhalation, rat)
Hexane 110-54-3	25 g/kg	3000 mg/kg	48000 ppm
Stoddard solvent 8052-41-3	-	-	-
Petroleum distillates, hydrotreated heavy naphthenic 64742-52-5	5000 mg/kg	2000 mg/kg	2.18 mg/L
Propane 74-98-6	-	-	658 mg/L
Butane 106-97-8	-	-	658 mg/L
Zinc oxide 1314-13-2	5000 mg/kg	-	-

Synergistic Products None known**Potential health effects****Sensitization** None known**Chronic toxicity** None known**Mutagenic effects** None known**Teratogenic effects** None known**Reproductive toxicity** None known**Target Organ Effects** Kidney. Liver. Central nervous system.**Carcinogenic effects** See Table Below.

Chemical Name	ACGIH OEL - Carcinogens	IARC	NTP - Known Carcinogens	NTP - Suspected Human Carcinogens	OSHA RTK Carcinogens
Hexane	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Stoddard solvent	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Petroleum distillates, hydrotreated heavy naphthenic	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Propane	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Butane	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Zinc oxide	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed

12. ECOLOGICAL INFORMATION**Hexane****Water Flea Data***water flea hEC50 48 (3.87 mg/L)*

Petroleum distillates, hydrotreated heavy naphthenic

Water Flea Data*Daphnia magna hEC50 48 (>1000 mg/L)***13. DISPOSAL CONSIDERATIONS****Disposal Information**

Full or partially full containers are considered hazardous waste. Dispose in accordance with federal, state, and local regulations.

14. TRANSPORTATION INFORMATION**DOT**

Consumer commodity, ORM-D

TDG

Consumer commodity, ORM-D

IMDG/IMO

UN1950 Aerosols, flammable, 2.1

IATA

ID8000 Consumer commodity, 9

MEX

UN1950 Aerosols, flammable, 2.1

15. REGULATORY INFORMATION

Chemical Name	US EPA SARA 313 Emission Reporting
Hexane	Listed
Zinc oxide	Listed

Chemical Name	New Jersey - RTK	Pennsylvania - RTK	California Prop. 65
Hexane	Listed	Listed	Not Listed
Stoddard solvent	Listed	Listed	Not Listed
Petroleum distillates, hydrotreated heavy naphthenic	Not Listed	Not Listed	Not Listed
Propane	Listed	Listed	Not Listed
Butane	Listed	Listed	Not Listed
Zinc oxide	Listed	Listed	Not Listed

Chemical Name	EINECS	DSL	NDSL	TSCA
Hexane	X	X	-	X
Stoddard solvent	X	X	-	X

Product code **19911**

Product name **White Lube**

Petroleum distillates, hydrotreated heavy naphthenic	X	X	-	X
Propane	X	X	-	X
Butane	X	X	-	X
Zinc oxide	X	X	-	X

CPR

This product has been classified in accordance with the hazard criteria of the Controlled Product Regulations and the MSDS contains all of the information required by the Controlled Product Regulations.

16. OTHER INFORMATION

NFPA

Health - 1
Flammability - 4
Reactivity - 0

HMIS

Health - 1
Flammability - 4
Physical Hazard - 0

Prepared By

J. Cameron, Regulatory Affairs
Coordinator

The information accumulated herein is believed to be accurate, but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.